



Anti-Slip™

Slip Resistant Additive for Liquid Coatings

Specifications

DESCRIPTION:

Anti-Slip slip resistant additive consists of micronized polymeric beads designed to improve traction on smooth or slippery surfaces. Once properly added to a liquid coating, the mixture can be applied by spray or other means to form a slip resistant, textured surface. When used properly, **Anti-Slip** can be used to replace external anti-slip mats and unsightly stick-on decals, while keeping in compliance with safety regulations. Unlike silica based products, **Anti-Slip** is low density, allowing it to stay suspended without settling.

USE:

Anti-Slip is a dry additive designed to be mixed with liquid coatings or sealants to be applied to horizontal surfaces exposed to foot traffic. **Anti-Slip** reduces slip hazards by increasing traction, especially in frequently wet areas or puddling water. Refer to the appropriate liquid coating data sheet for more information on usage.

ADVANTAGES:

- Reduces slip hazards by increasing traction and slip resistance
- Can be added to liquid coatings or sealants without settling
- Does not yellow or affect coating performance
- Very cost effective - typical use is less than one half ounce per tub

LIMITATIONS:

- Not intended for vehicle traffic
- Excess material may reduce gloss and produce a rough texture

Properties

VOC: [product alone] None

FLASH POINT: [setaflash] None

APPEARANCE: Fine White Powder

SPECIFIC GRAVITY: [average] 1.11
Particle size as packaged 50 microns

COVERAGE: [average] 30 sq ft/oz

COLOR AVAILABILITY:

Anti-Slip slip resistant additive appears as a powder when packaged. After being added to chosen liquid coating or sealant, **Anti-Slip** assumes color of coating or sealant.

ORDER CODE: W1-14

PACKAGING: Quart container
One, 1 quart container 1 lb

Shipping & Handling

SHIPPING DESCRIPTION: [CFR 49]

Ground, Air, Vessel Not regulated
Required Marking PAINT UN1263

IMDG PACKAGING & STOWAGE: ... Not regulated

UNIFORM FIRE CODE: [CFR 49] Non combustible

STORAGE TEMPERATURE: 35° F - 120° F

SHELF LIFE: [warranted] 1 YEAR

HMIS RATINGS: H - 1; F - 0; R - 0; PP - H

Anti-Slip™

Slip Resistant Additive for Liquid Coatings

Application Data

REQUIREMENTS

- Follow manufacturer’s recommendations for coating or sealant used.

PRIMING:

- Follow manufacturer’s recommendations for coating or sealant used.

FILM DEVELOPMENT & THICKNESS:

Anti-Slip is used at extremely low levels. Use only enough to achieve desired roughness. Improper mixing may slow solvent release and therefore retard cure. Typical substrates include bath or kitchen surfaces prone to wetness, such as ceramic, porcelain glazed or unglazed tile, and various metals. Actual application rates may vary, but use approximately 2 grams per tub.

MIXING-THINNING:

Prewet **Anti-Slip** with **AT60** urethane thinner in equal volumes then add slurry to chosen coating. Mix by hand for 2-3 minutes.

APPLICATION:

Follow manufacturer’s recommendations for coating or sealant used.
 May be sprayed or rolled, using 3/8” nap or less, solvent resistant roller size. Use solvent resistant sprayer when applying. A slightly larger tip may be necessary to accomodate 50 micron particles.

CLEANUP: None

If spillage occurs while dry, sweep or brush to remove **Anti-Slip** from surface.

Health & Safety

CAUTION:

DO NOT INGEST.

FIRST AID:

Should eye contact occur, flush with plenty of water for at least 15 minutes and get medical attention if vision is disturbed.

THIS PRODUCT IS FOR PROFESSIONAL USE ONLY.

KEEP THIS PRODUCT OUT OF THE REACH OF CHILDREN.

WARRANTY: The statements made herein, on labels, product bulletins, or by any of Triangle Coatings', Inc. employees or agents concerning this product are given for general information only. Due to variables beyond Triangle's control in application, surface preparation, surface temperature, humidity and other variable factors Triangle assumes no liability for any claim that may arise out of the use of its products and disclaims any warranty expressed or implied relating to the storage, application, thinning, merchantability, Buyer's assumption of performance, and the fitness for a particular purpose. Receipt of products from Triangle or its agents constitutes acceptance of the terms of this warranty. In the event that Triangle finds that the product delivered is not of Triangle's standard quality, Triangle will at its sole discretion, either replace the product or refund the purchase price. Triangle's choice of one of these remedies shall be the Buyer's sole remedy. Triangle will under no circumstances be liable for consequential damages, except insofar as liability is mandated by law. Triangle will deliver products at agreed times insofar as it is reasonably able to do so, but it will not be liable for failure to deliver on time when the failure is beyond its reasonable control.