



**White Mountain™**

# Bubble Gum Release

*Liquid Release Agent for Concrete Stamps and Imprinting Tools*

## SPECIFICATIONS

### DESCRIPTION:

**Bubble Gum Release** is a scented release agent specially formulated for use when imprinting fresh concrete or overlays. The release agent forms a bond breaking barrier between tools and concrete to promote a clean, easy release of stamping, texturing, and imprinting tools. Used to prevent paste transfer from wet cementitious surfaces, **Bubble Gum Release** is an alternative to powder release agents and features an appealing bubble gum scent to help identify the product. It is safe for use on newly colored or uncolored concrete and is easy to apply. **Bubble Gum Release** evaporates completely, leaving concrete surfaces free of residue and ready for sealing.

### USE:

**Bubble Gum Release** can be used for any interior or exterior concrete stamping, texturing, or imprinting.

**Bubble Gum Release** is ideal for use with:

- fresh concrete stamping
- cementitious overlay imprinting
- mat-type imprinting tools
- finishing tools
- embossing skins
- antiquing/highlighting decorative effects

Product results will vary by substrate and application method. ***It is the user's responsibility to determine the suitability and performance of this product for their application.***

### ADVANTAGES:

- Easily releases imprinting tools from concrete
- Leaves no residue
- Prolongs life of tools
- Appealing bubble gum scent

### LIMITATIONS:

- Evaporates quickly
- To comply with SCAQMD regulations, this product is limited to a maximum use of 6 gallons per day

## PROPERTIES

**VOC:** [photochemically reactive] ... 778 g/l – (6.49 lbs/gal)

**FLASH POINT:** [setaflash] ..... 125° F

### APPEARANCE:

Wet ..... clear

Dry ..... n/a

**ODOR:** ..... bubble gum

**WEIGHT PER GALLON:** [average] ..... 6.54 lbs

### SOLIDS:

By Weight ..... 0%

By Volume ..... 0%

### COVERAGE:

Usage Rate ..... 160 sq ft/gal

For more exact usage rates, apply measured quantities of product to 1 square foot of substrate. Repeat until saturation obtained. Saturation obtained when material begins to pool on surface.

**ORDER CODE:** ..... W3-05

### PACKAGING:

Four 1 gallon plastic jugs per case

5 gallon pails

# Bubble Gum Release

## Liquid Release Agent for Concrete Stamps and Imprinting Tools

### APPLICATION DATA

#### SURFACE PREPARATION:

- Before use, thoroughly test this product on a sample to assure performance and appearance.

#### APPLICATION:

For small areas, use an appropriate handheld sprayer to apply all coatings. Consult your local equipment supplier for recommendations. Do not allow coating to dry on spray tip. If this occurs, soak the tip in the recommended cleanup solvent.

- Apply liberally to concrete surface once concrete reaches the drying stage desirable for imprinting.
- Apply uniformly over areas of 10 to 15 square feet at a time to avoid evaporation before mats are placed. Texture of tool surface may affect amount needed; rough surfaces may require more release agent than flat surfaces.
- Use imprinting tools as normal.
- **Bubble Gum Release** evaporates and must be reapplied periodically/as needed to keep tools from sticking to wet cementitious surfaces.
- **Bubble Gum Release** may also be used with pigment additives for adding decorative effects to concrete or cementitious surfaces.

#### Application Caution:

Cover all plants, trees, grasses, and shrubs to protect from overspray. If overspray occurs, wash off with water immediately. Mask areas that may be affected by overspray.

**CLEANUP:** ..... rinse tools with clean water

### HEALTH & SAFETY PRECAUTIONS

#### WARNING:

**COMBUSTIBLE LIQUID AND VAPOR.** Harmful vapor if inhaled. Vapor may affect the brain or nervous system causing dizziness, headache, or nausea and can cause nose and throat irritation. Liquid contact with eye and skin may cause irritation. Do not ingest. Keep away from sparks, heat, or open flame. Use with adequate ventilation. Avoid breathing of vapor. Avoid contact with eyes and skin. Wash hands thoroughly after using and before eating and smoking. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor levels are below applicable limits. Follow respirator manufacturer's directions for use. If spillage has occurred, absorb and dispose of according to local regulations. **Contains:** Petroleum Naphtha, CAS#64742-88-7.

#### FIRST AID:

Should eye contact occur, flush with plenty of water for at least 15 minutes and get medical attention if vision is disturbed. For skin, wash thoroughly with soap and water. If swallowed, seek medical attention immediately. **DO NOT** induce vomiting.

**THIS PRODUCT FOR PROFESSIONAL USE ONLY.  
KEEP OUT OF THE REACH OF CHILDREN.**

### SHIPPING & HANDLING

#### SHIPPING DESCRIPTION: [CFR 49]

**Domestic Ground** ..... Not Regulated  
**Air & Vessel** ..... Paint, 3, UN1263, PG III  
 Required Label ..... FLAMMABLE LIQUID  
 Required Marking ..... PAINT UN1263

#### IMDG PACKAGING:

FLAMMABLE LIQUID, class 3.2, UN1263, III

**IMDG STOWAGE:** ..... Category A

**UNIFORM FIRE CODE:** [CFR 29] ..... CLASS II

**STORAGE TEMPERATURE:** ..... 120°F max

**SHELF LIFE:** [warranted] ..... 1 YEAR

**HMIS RATINGS:** ..... H - 2; F - 2; R - 0; PP - H

**WARRANTY:** The statements made herein, on labels, product bulletins, or by any of Triangle Coatings', Inc. employees or agents concerning this product are given for general information only. Due to variables beyond Triangle's control in application, surface preparation, surface temperature, humidity and other variable factors Triangle assumes no liability for any claim that may arise out of the use of its products and disclaims any warranty expressed or implied relating to the storage, application, thinning, merchantability, Buyer's assumption of performance, and the fitness for a particular purpose. Receipt of products from Triangle or its agents constitutes acceptance of the terms of this warranty. In the event that Triangle finds that the product delivered is not of Triangle's standard quality, Triangle will at its sole discretion, either replace the product or refund the purchase price. Triangle's choice of one of these remedies shall be the Buyer's sole remedy. Triangle will under no circumstances be liable for consequential damages, except insofar as liability is mandated by law. Triangle will deliver products at agreed times insofar as it is reasonably able to do so, but it will not be liable for failure to deliver on time when the failure is beyond its reasonable control.

*Product Data Sheets are periodically updated to reflect new information relating to the product. It is important to obtain the most recent Product Data Sheet for the product being used before application.* WMW305-10/12-005

**TRIANGLE COATINGS, INC.** 4763 Bennett Drive, Livermore, CA 94551-4804 • Tel: 925-583-0800 • Fax: 925-583-0880 • [www.tricoat.com](http://www.tricoat.com)